



# Pressure Switches



## PS Series

### Pressure Type Waterflow Alarm/Supervisory Switch

- NEMA 4 solid metal enclosure
- Factory installed neoprene gasket
- Pressure range: 4-15 psi (PS10), 5-30 psi (PS15), 10-60 psi (PS25 & PS40), 25-175 psi (PS120)
- 300 psi system pressure rated
- ½" male NPT fitting
- Two ½" knockouts for dual voltage applications
- Isolated wiring chambers eliminate NEC questions regarding multi-voltage applications
- Factory set for operation at:
  - PS10 *Pressure Increase at 6 psi*
  - PS15-2 *Pressure decrease at 10 psi, Pressure increase at 20 psi*
  - PS25-2 *Pressure decrease at 18 psi, Pressure increase at 28 psi*
  - PS40-1 *Pressure Decrease at 30 psi*
  - PS40-2 *Pressure Increase at 50 psi, Pressure Decrease at 30 psi*
  - PS120-1 *Pressure Decrease at 110 psi*
  - PS120-2 *Pressure Increase at 130 psi, Pressure Decrease at 110 psi*
- 5-year warranty
- Listings: UL, cUL, CSFM, FM, LPC, NYMEA, and CE

*VdS* is listed with UL, FM, VdS, CUL, LPCB, and CSFM



Two 1/2" knockouts for dual high/low voltage functions or in/out wiring

Complies with NEC 760.55



Single captive tamper-proof screw for quick access and easy installation

Compact design for easy installation in tight spaces and rain-lip for protection against the elements



Separate wiring chambers creating the only NEC 760.55 code compliant pressure switch in the industry