

## DATA SHEET

## 36 SERIES INSULATED ACCESS DOOR

# Insulated Fire-Rated ACCESS DOOR

Designed for wall and ceiling applications, this fire-rated Insulated Access Door is UL and Warnock-Hersey listed. Engineered with mineral fiber to assist in reducing heat transfer in the event of a fire.

### FEATURES

**FIRE-RATED** Independently tested and labeled for 1-1/2 hours for wall applications and 3 hours for ceiling applications.

**EASY OPERATION** This self-closing door features an inside knurled knob latch release is easy to operate.

**CUSTOM SIZING** Custom sizes available from 6 inches by 6 inches to 48 inches by 48 inches.

### DETAILS

**DOOR** 20 gauge Steel, Self-Closing

**FRAME** 16 gauge Steel

#### SIZE

- Min: 6 inches by 6 inches
- IT Max: 24 inches by 72 inches or 48 inches by 48 inches
- IW/IP Max: 36 inches by 48 inches

**INSTALLATION** Ceiling or Wall

#### HINGE

- Flush Continuous Piano

**FINISH** White Powder Coat

**INSULATION** 2 inch Thick, Fire-Rated Mineral Fiber, R-8

#### CERTIFICATION

- UL listed "B" label for 1-1/2 hours (Wall)
- Warnock-Hersey listed for 3 hours (Ceiling)



### MATERIALS FLANGE

### LATCHES



White  
Powder Coat



1 inch Flange



Knurled  
Knob