



TEXPEN[®] Marker

Industrial Steel Ball Tip Paint Marker

HANDLING

- Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Write sharp, defined, bright marks on any surface including metal, plastic, glass, concrete, rubber and more
- Ergonomically correct marker that enables you to mark at all angles, even upside down
- Marker retains its shape unlike tube-style markers
- Paint flow is controlled by the pressure bulb at the end of the barrel
- Drying Time: 25 – 35 minutes
- Available in both fine and medium tip

MATERIALS COMPATIBILITY

- Safe on most surfaces
- Surface test should be run to determine compatibility prior to use



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Aromatic
Flash Point	108.0 °F (42.2 °C) Tag Closed Cup
Boiling Point / Range	318 - 338 °F (158.89 - 170 °C)
VOC Content	28.97 - 35.58%
Evaporation Rate	< 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Water Solubility	Slightly soluble

AVAILABLE IN

Color	Marker Tip	Units/Case	Part #
yellow	fine, steel	48	608520Y
white	fine, steel	48	608520W

