

MULTI-PURPOSE

# ABC DRY CHEMICAL



**STRIKE FIRST**  
FIRE EXTINGUISHERS



**WHEN  
SECONDS  
COUNT.**



## Built Tough and Ready to Serve

- Modified universal valve body
- Accepts both pin or fork wall hooks
- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)
- 90% MAP (mono ammonium phosphate powder)

**STRIKE FIRST ABC Multi-Purpose  
Dry Chemical Fire Extinguishers  
are designed for:**



**A** WOOD  
PAPER  
& CLOTH



**C** ELECTRICAL  
EQUIPMENT



**B** FLAMMABLE  
LIQUIDS  
& GASES



**MEETS OR EXCEEDS:**  
ANSI/UL 299 & 711



LISTED  
HOMOLOGUÉ

**MEETS OR EXCEEDS:**  
CAN/ULC-S504 & S508





## Manufacturing Fire Equipment for over 35 Years



| CAPACITY          | 2.5 lbs                 | 5 lbs                             | 5 lbs                             | 10 lbs                           | 20 lbs                            | 30 lbs                           |
|-------------------|-------------------------|-----------------------------------|-----------------------------------|----------------------------------|-----------------------------------|----------------------------------|
| Model No.         | 70600212                | 70600500                          | Call                              | 70601000                         | 70602000                          | Call                             |
| UL/ULC Rating     | 1-A : 10-B : C          | 3-A : 10-B : C                    | 3-A : 40-B : C                    | 6-A : 80-B : C                   | 10-A : 120-B : C                  | 10-A : 120-B : C                 |
| U.S.C.G. Approval | Type B:C Size I         | Type A Size II, Type B:C Size I   | Type A Size II, Type B:C Size I   | Type A Size II, Type B:C Size II | Type A Size II, Type B:C Size III | Type A Size II, Type B:C Size IV |
| Range             | 8-10 ft (2.5-3 m)       | 8-10 ft (2.5-3 m)                 | 8-10 ft (2.5-3 m)                 | 10-15 ft (3-4.5 m)               | 10-15 ft (3-4.5 m)                | 10-15 ft (3-4.5 m)               |
| Discharge Time    | 9 sec                   | 14.5 sec                          | 14.5 sec                          | 21 sec                           | 28 sec                            | 28 sec                           |
| PSI               | 150                     | 195                               | 195                               | 235                              | 235                               | 195                              |
| Height            | 15 1/4" (39 cm)         | 15 1/4" (39 cm)                   | 16 7/8" (43 cm)                   | 21 1/4" (54 cm)                  | 24" (61 cm)                       | 30 3/4" (78 cm)                  |
| Width             | 3 3/4" (9.5 cm)         | 6 3/4" (17 cm)                    | 6 3/4" (17 cm)                    | 8" (20.3 cm)                     | 9 1/2" (24 cm)                    | 9 1/2" (24 cm)                   |
| Diameter          | 3 1/8" (8 cm)           | 4 1/4" (11 cm)                    | 4 1/4" (11 cm)                    | 5 1/8" (13 cm)                   | 7 1/8" (18 cm)                    | 7 1/8" (18 cm)                   |
| Weight            | 4 1/2 lb (2 kg)         | 10 1/2 lb (4.8 kg)                | 10 1/2 lb (4.8 kg)                | 19 1/4 lb (8.8 kg)               | 35 1/4 lb (16.1 kg)               | 50 1/3 lb (22.8 kg)              |
| Chrome Option     | YES                     | YES                               | YES                               | -                                | -                                 | -                                |
| Standard Bracket  | Wall or Vehicle/ Marine | Wall or Vehicle/ Marine           | Wall or Vehicle/ Marine           | Wall or Vehicle/ Marine          | Wall                              | Wall                             |
| Optional Brackets | Wall<br>UP2<br>UP-DB    | UB5<br>UB5-DB<br>UP5-MD<br>HDVB-1 | UB5<br>UB5-DB<br>UP5-MD<br>HDVB-1 | UP-10MD<br>HDVB-2                | HDVB-3                            | HDVB-4<br>HD-CART                |